**Note:** This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.



Choose certainty.
Add value.

#### **SUBJECT:**

Testing of wafer type cast iron butterfly valves submitted by KVS Valves Pte Ltd.

#### **TESTED FOR:**

KVS Valves Pte Ltd 7030 Ang Mo Kio Avenue 5,#08-55 North Star @AMK Singapore 569880

Attn: Mr. Leroy Nai

#### **TEST METHOD:**

- 1. BS EN 593:2009+A1:2011 Specification for Industrial valves-Metallic butterfly valves.
- 2. BS EN 558:2008+A1:2011 Specification for Industrial valves-Face-to-face and centre-to-face dimensions of metal valves for use in flanged pipe systems
- **3.** BS EN 12266-1:2012 Industrial valves-Testing of metallic valves-Part 1 :Pressure tests,test procedures and acceptance criteria-Mandatory requirements.

#### **TESTS CONDUCTED:**

- 1. Dimensional measurements
- Hydrostatic pressure test













LA-2007-0380-A LA-2007-0381-F LA-2007-0382-B LA-2007-0383-G LA-2007-0383-G LA-2010-0464-D The results reported herein have been performed in accordance with the terms of accreditation under the Singapore Accreditation Council. Inspections/Calibrations/Tests marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our inspection body/laboratory.



#### **SAMPLE DESCRIPTION:**

Six samples of wafer type cast iron butterfly valve (Model: KVS 300) PN 16 of size DN 65mmØ, 80mmØ, 100mmØ, 125mmØ, 150mmØ and 200mmØ were received.



#### **EMBOSSED MARKINGS ON VALVE BODY:**

KVS 300 CI PN16 DN 65 ,DN 80, DN 100, DN 125, DN 150, DN 200

#### **LABEL MARKINGS:**

Body: Cast Iron Seat: EPDM Disc: DI

Connection: PN 16 Shaft: SS 416

## **DATE TESTED:**

20/01/2017 to 25/01/2017

July July Or



## **RESULTS:**

## (1) Dimensional Measurements

Sample Reference	KVS-300		BS EN 593:2009+A1:2011 Cross Reference to	
	65mmØ	80mmØ	BS EN 558:2008+A1:2011 (Table 2 & 3a) Requirements	
Face to Face Dimension	45.0	46.0	46±2	46±2

Sample Reference	KVS-300		BS EN 593:2009+A1:2011 Cross Reference to	
	100mmØ	125mmØ	BS EN 558:2008+A1:2011 (Table 2 & 3a) Requirements	
Face to Face Dimension	53.0	54.8	52±2	56±2

Sample Reference	KVS-300		BS EN 593:2009+A1:2011 Cross Reference to	
	150mmØ	200mmØ	BS EN 558:2008+A1:2011 (Table 2 & 3a) Requirements	
Face to Face Dimension	56.5	60.6	56±2	60±2

## (2) Hydrostatic Pressure Tests

Sample Reference	KVS-300		BS EN 593:2009+A1:2011	
	65mmØ	80mmØ	Cross Reference to BS EN12266-1:2012 Requirements	
Hydrostatic test pressure of 17.6 bar applied on valve seat	Pass	Pass	The valve shall withstand the hydrostatic test pressure without showing any signs of leakage.	
Hydrostatic test pressure of 24 bar applied on valve body	Pass	Pass		

July Brown



#### **RESULTS:**

Sample Reference	KVS-300		BS EN 593:2009+A1:2011	
	100mmØ	125mmØ	Cross Reference to BS EN12266-1:2012 Requirements	
Hydrostatic test pressure of 17.6 bar applied on valve seat	Pass	Pass	The valve shall withstand the hydrostatic test pressure withou	
Hydrostatic test pressure of 24 bar applied on valve body	Pass	Pass	showing any signs of leakage.	

Sample Reference	KVS-300		BS EN 593:2009+A1:2011	
	150mmØ	200mmØ	Cross Reference to BS EN12266-1:2012 Requirements	
Hydrostatic test pressure of 17.6 bar applied on valve seat	Pass	Pass	The valve shall withstand the	
Hydrostatic test pressure of 24 bar applied on valve body	Pass	Pass	hydrostatic test pressure without showing any signs of leakage.	

#### **CONCLUSION:**

The above results of the tested sample meet the requirements BS EN 593:2009+A1:2011, BS EN 558:2008+A1:2001 and BS EN 12266-1:2012 specification.

Lee Ngiap Boon Testing Officer Cliff Yew Senior Associate Engineer Industrial Group Mechanical Centre



Please note that this Report is issued under the following terms:

- 1. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
- 2. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
- 3. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
- 4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
- 5. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

